

12SB20C

Specifications

Nominal Voltage (V) 12V

Nominal Capacity

20hour rate (1.0A	to	10.50V)	20Ah
10hour rate (2.0A	to	10.50V)	19Ah
5hour rate (3.4A	to	10.20V)	17Ah
1C (20A	to	9.60V)	12.67Ah
3C (60A	to	9.60V)	8Ah

Weight Approx.6.080kg(13.38Lbs.)

Internal Resistance (at 1KHz) 10 m

Maximum Discharge Current for 5 seconds : 327A

Operating Temperature Range

Charge	-15 (5)	to	40 (104)
Discharge	-15 (5)	to	50 (122)
Storage	-15 (5)	to	40 (104)

Charge Retention (shelf life) at 20 (68)

1 month	92
3 month	90
6 month	80

Charging Methods at 20 (68)

Cycle use:

Charging Voltage 14.4 to 15.0V
Maximum Charging Current 6A

Standby use :

Float Charging Voltage 13.50 to 13.80V

Life expectancy :

Cycle Use

100% depth of discharge 225 cycles
80% depth of discharge 250 cycles
50% depth of discharge 750 cycles

Standby Use 3~5years

Case Material ABS

(Option 94-HB & 94V-0 flame retardant case)

Terminal F3

Dimensions

