



1 2 3 4 5 6

A

B

C

D



This drawing and the designs so represented are the copyright property of Master Instruments Pty Ltd. The drawing shall not be copied, loaned or issued without the express written permission of a duly authorised representative of Master Instruments Pty Ltd.

Technical Data

Safety Board (PCM)

PCM	MIPCM-1SXP4APTC
Over Charge Detection Voltage	4.275V ± 0.025V
Over Charge Release Voltage	4.175V ± 0.025V
Over Discharge Detection Voltage	2.3V ± 0.05V
Over Discharge Release Voltage	2.4V ± 0.05V
Over Current Detection Current	3A ± 1A
Max Discharge Current	4A
Short Circuit Protection	Charge or Open Circuit
Protection Circuit Resistance	30 - 60mΩ
PTC Resettable Fuse	MF-MSMF260 (Bourns)
Thermistor	10K Ω NTC Beta 3435k/ohm
Chemistry	Lilon
Configuration	1S1P
Voltage	3.6V
Capacity	3.35Ah
Energy	12.06Wh
Weight	48g
Rated Discharge	650mA (C/5)
Max Discharge Continuous	PCM: 4A
	Cell: 4.875A
Charge Rate	1.625A
Operating Temperature Range	Charge: 0 - 45°C
	Discharge: -20 °C - +60°C
Charge Voltage	4.2V ± 0.03V
Discharge End Voltage	2.5V
Connector	JST PHR-3
Suits Mating Connector	B3B-PH-K-S / S3B-PH-SM4-TB

PART NO	RL804	STOCK CODE	88003-101	RevNo	1 (15/12/2016)
CELL TYPE	NCR18650BF	RECOMMENDED CHARGER	3P10-L1004 or FY042xxx	DATE	07/10/15
				PAGE	1 OF 1

1 2 3 4 5 6